

Direct Plug-In USB Headsets



Order Code
JPL-502S-USB

Order Code
JPL-501S-USB

TECHNICAL DATA

Microphone:

Directional:	Bi-directional
Impedance:	Max. 2.2KΩ 1KH(RL=2.2KΩ)
Sensitivity:	-43±3dB RL=2.2KΩ Vs=2.0V (DC)
Frequency Range:	100-10000Hz
Operating Temp:	-25°C~+70°C
Storage Temp:	-40°C~+80°C

Speaker:

Impedance:	150Ω ±15% at 0.1 V1000Hz
Sound pressure:	129dB ± 3dB at 1000HZ
Frequency range:	FO ~20KHZ(±10dB) FO: 210Hz ± 20%
Operating Temp:	-25°C 50°C
Storage Temp:	-25°C 60°C



USB-A



CLOTHING CLIP



JPL-501S / 502S

Improved sound quality and a flexible microphone boom arm with **Surround Shield™** noise cancellation.

Overview

Features	Single or dual ear
	Left / right ear side compatible
	Surround Shield™ noise cancelling microphone
	Clear, crisp sound
	'Put and stay' ratchet microphone boom arm
	Overhead, sure-fit fully adjustable headband
	Fitted with 50mm leatherette ear cushions for maximum all day comfort
What's included	Clothing clip, Quick Start Guide and In-Line Control with Volume & Mute
Headset Weight	Mid-weight Headset, ~ 70g / ~106g
Connection	USB-A
Compatibility	Direct Plug-in
Certifications	CE, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 40
EAN:	JPL-501S-USB: 5060126958055, JPL-502S-USB: 5060126958079
SKU:	JPL-501S-USB: 575-329-0013, JPL-502S-USB: 575-329-002

